



HIGH QUALITY

CEJN's high quality hose and cable reels contain a CEJN polyurethane hose or rubber cable. The reels are easy to manoeuvre and can be ceiling or wall-mounted and offer full, 300 degree, movement. A robust exterior housing protects the hose or cable and reel mechanism and the feeding action works flawless and tangle free. A stop function can be activated if full continuous feeding is not necessary at the time.

FEATURES AND BENEFITS

- Slow Retract
- Hose Guide
- Lowest Pressure Drop in the Market
- Quicker Hose Change
- New Hose Stopper

SPECIFICATIONS

PART NUMBER	MAX. WORKING PRESSURE	TEMPERATURE RANGE	MEDIA
C199112083	16 bar	-20°C - +60°C	Air
C199112183	16 bar	-20°C - +60°C	Air
C199112020	16 bar	-20°C - +60°C	Air
C199112022	16 bar	-20°C - +60°C	Air
C199112120	16 bar	-20°C - +60°C	Air
C199112130	16 bar	-20°C - +60°C	Air
C199112132	16 bar	-20°C - +60°C	Air
C199112140	12 bar	-20°C - +60°C	Air
C199112040	12 bar	-20°C - +60°C	Air
C199112150	12 bar	-20°C - +60°C	Air
C199112230	16 bar	5°C - +60°C	Water
C199112240	12 bar	5°C - +60°C	Water

COMPRESSED AIR HOSE REELS



New

COMPRESSED AIR HOSE REEL 320 ESAFE CONNECTION

610

PART NUMBER	ID X OD	LENGTH	PRICE
C199112082	8 x 12 mm	10 m	CTCP*
C199112182	8 x 12 mm	17 m	CTCP*

1/4" BSPT MALE CONNECTION

C199112020	8.0 x 12.0 mm	7 m	CTCP*
C199112022	8.0 x 12.0 mm	10 m	CTCP*
C199112120	8.0 x 12.0 mm	17 m	CTCP*
C199112130	9.5 x 13.5 mm	14 m	CTCP*

1/4" BSPT ANTISPARK CONNECTION

C199112132	9.5 x 13.5 mm	14 m	CTCP*
------------	---------------	------	-------

1/2" BSPT MALE CONNECTION

C199112140	11 x 16 mm	12 m	CTCP*
C199112040	11 x 16 mm	5 m	CTCP*
C199112150	13 x 18 mm	10 m	CTCP*

WATER HOSE REELS



New

WATER HOSE REEL 1/4" BSPT CONNECTION

610

PART NUMBER	ID X OD	LENGTH	PRICE
C199112230	9.5 x 13.5 mm	14 m	CTCP*

1/2" BSPT CONNECTION

C199112240	11 x 16 mm	12 m	CTCP*
------------	------------	------	-------

ELECTRIC HOSE REELS



New

ELECTRIC HOSE REEL SCHUKO PLUG

610

PART NUMBER	ID X OD	LENGTH	PRICE
C199112310	3 x 1.5 mm	17 m	CTCP*

CH PLUG

C199112311	3 x 1.5 mm	17 m	CTCP*
------------	------------	------	-------